IN THE CLAIMS

This listing of claims replaces all prior listings:

- 1. (Previously Presented) A liquid crystal display apparatus comprising:
- a plurality of vertical signal lines;
- a plurality of horizontal signal lines;
- a display pixel located where one of the vertical signal lines and one of the horizontal signal lines intersect; and

shield wires on opposite sides of each of the vertical signal lines and on opposite sides of each of the horizontal signal lines,

wherein.

- a potential of the shield wires is set at a value at which the display pixel is displayed in black, such that when a defect occurs it is not recognized by a human eye.
 - 2. (Previously Presented) A liquid crystal display apparatus comprising:
 - a plurality of vertical signal lines;
 - a plurality of horizontal signal lines;
- a display pixel located where one of the vertical signal lines and one of the horizontal signal lines intersect; and

shield wires on opposite sides of each of the vertical signal lines and on opposite sides of each of the horizontal signal lines,

wherein.

a potential of said shield wires is set at a value at which the

display pixel is displayed in black or nearly black, such that when a defect occurs it is

Response to June 12, 2009 Office Action

Application No. 10/599,773

Page 3

not recognized by a human eye.

3. (Previously Presented) A liquid crystal display apparatus as claimed in claim 1 or 2,

wherein in a normally black mode, the potential of said shield wire is set at a value equal to or

nearly equal to a potential of a common electrode.

4. (Previously Presented) A liquid crystal display apparatus as claimed in claim 1 or 2,

wherein in a normally white mode, the potential of said shield wire is set at a maximum value, a

minimum value or a value approximate thereto of a voltage to be applied to the display pixel.

- 3 -